

Forced Air Oven

TFO-5

PART ID: CTF523



Capacity	4.9 cu.ft. (138.0 liters)
Interior Dimensions W x D x H	21.0" x 19.4" x 20.7" 533 x 494 x 527 mm
Exterior Dimensions W x D x H	31.4" x 28.1" x 38.8" 798 x 714 x 986 mm
Unit Weight	208 lb (94.3 kg)
Shipping Weight	258 lb (117 kg)
Shelves	2 standard, 9 total
Maximum Weight Per Shelf	50 lb / 22.6 kg
Permitted Total Load	200 lb / 91 kg
Standard Door Gasket	Woven Fiberglass
Access Port	1.75" Rear
Controls	Watlow PM9 Plus
Warranty	2 Year Limited Warranty
Interior Construction	300 series stainless steel
Exterior Construction	20 gauge steel, powder coated
Vertical Clearance	24.0" (600 mm)
Wall Clearance, Each Side	6.0" (152 mm)
Wall Clearance, Rear	12.0" (300 mm)
Electrical, 50/60Hz, AC, 1Ø	
Voltage	110V-120V
Full Load Amps	14
Nominal Power (watts @150°C)	700
Recommended Breaker, Amps	15
NEMA Plug Supplied	5-15P
Energy Consumption (kWh/day)	
At 80°C	7.5
At 150°C	13.5
At 306°C	23.8
Temperature Range 20°C above ambient to 306°C	
Heat-Up Time — Minutes to 80°C	9
Heat-Up Time — Minutes to 150°C	28
Heat-Up Time — Minutes to 306°C	130
Recovery after Door Opening (30 sec.) — Minutes to 80°C	2
Recovery after Door Opening (30 sec.) — Minutes to 150°C	4
Recovery after Door Opening (30 sec.) — Minutes to 306°C	45
Recovery after Door Opening (60 sec.) — Minutes to 80°C	3.5
Recovery after Door Opening (60 sec.) — Minutes to 150°C	6
Recovery after Door Opening (60 sec.) — Minutes to 306°C	57
Temperature Uniformity	
At 80°C	0.75°C
At 150°C	1.8°C
At 306°C	4.5°C
Air Flow Performance	
Air Changes Per Hr at Max	180
Flow Rate (CFM)	15.2



0740577 6/24

Contact Cascade TEK

sales@cascadetek.com • cascadetek.com • +1-971-371-4096

